



## Probe Mount TM0393X

The high-pressure probe mount, TM0393X, works with Provibtech's TM0180 and TM0110 reverse mount probes. The housing mounts on the machine surface for easy installation. The housing is made of aluminum (copper free) and stainless steel which sustain harsh environments. The high-pressure probe mount, TM0393X, can be used for up to 2000psi (15Mpa)



### Features

- ✓ Doesn't require to open the machine case when replacing the reverse probes
- ✓ Flexible installation as penetration length is adjustable +/-13mm (0.5 in)
- ✓ Brilliant appearance and sustainable material

### Order Information

#### TM0393X-AAA-BBB-C-D

AAA: Probe Penetration Depth

The depth starts from 25 mm (1.0 in)

AAA+BBB < 700 mm (27.6 in)

Order in increments of 5mm

For example: AAA=075 = 75mm

BBB: Stand off Adapter

BBB=000:No stand off adapter required

Starting from 40mm (1.57 in)to 200mm(7.87in)

Order in increments of 10mm (0.39in)

For example: BBB=015=150mm

C: Probe Thread

C=0: M10x1

C=1: 3/8-24"

D: Pressure Option

D=0: Not required

D=1:High-pressure probe mount

\*One 3/4"NPT Stainless plug is included as default

### Accessories

#### PT500-19

Cable seal grip





**Schematic Diagram**

